

RProtoBuf 0.4.3: Quick Reference Guide

Romain François

Dirk Eddelbuettel

Murray Stokely

August 25, 2015

```
example proto file  package tutorial;
option java_package = "com.example.tutorial";
option java_outer_classname = "AddressBookProtos";
message Person {
  required string name = 1;
  required int32 id = 2;
  optional string email = 3;
  enum PhoneType {
    MOBILE = 0;
    HOME = 1;
    WORK = 2;
  }
  message PhoneNumber {
    required string number = 1;
    optional PhoneType type = 2 [default = HOME];
  }
  repeated PhoneNumber phone = 4;
  extensions 100 to 199;
}
message AddressBook {
  repeated Person person = 1;
}
service EchoService {
  rpc Echo (Person) returns (Person);
}
```

read proto description files

```
> readProtoFiles( "somefile.proto" )
> readProtoFiles( dir = somedir )
> readProtoFiles( package = AnRPackage )
```

create a message

```
> message <- new( tutorial.Person, id = 0,
+   name = "Romain Francois",
+   email = "francoisromain@free.fr" )
```

serialize a message to a file or binary connection

```
> tf1 <- tempfile()
> message$serialize( tf1 )
> tf2 <- tempfile()
> con <- file( tf2, open = "wb" )
> message$serialize( con )
> close(con)
> message$serialize( NULL )
[1] 0a 0f 52 6f 6d 61 69 6e 20 46 72 61 6e 63 6f
[16] 69 73 10 00 1a 16 66 72 61 6e 63 6f 69 73 72
[31] 6f 6d 61 69 6e 40 66 72 65 65 2e 66 72
```

read a message from a file or binary connection

```
> tutorial.Person$read( tf1 )
message of type 'tutorial.Person' with 3 fields set
> con <- file( tf2, open = "rb" )
> tutorial.Person$read( con )
message of type 'tutorial.Person' with 3 fields set
```

Get/Set fields

```
> email <- message$email
> message$id <- 2
> message[[ "name" ]] <- "Romain"
> id <- message[[ 2 ]]
```

Message methods

| | |
|---------------|--|
| has | Indicates if a message has a given field. |
| clone | Creates a clone of the message |
| isInitialized | Indicates if a message has all its required fields set |
| serialize | serialize a message to a file or a binary connection or retrieve the message payload as a raw vector |
| clear | Clear one or several fields of a message, or the entire message |
| size | The number of elements in a message field |
| bytesize | The number of bytes the message would take once serialized |
| swap | swap elements of a repeated field of a message |
| set | set elements of a repeated field |
| fetch | fetch elements of a repeated field |
| add | add elements to a repeated field |
| str | the R structure of the message |
| as.character | character representation of a message |
| toString | character representation of a message (same as as.character) |
| update | updates several fields of a message at once |
| descriptor | get the descriptor of the message type of this message |

```
> writeLines( message$toString() )
name: "Romain"
id: 2
email: "francoisromain@free.fr"
```

More info

| | |
|---------------|---|
| full vignette | vignette("RProtoBuf") |
| protobuf | http://code.google.com/p/protobuf/ |
| RProtoBuf | http://r-forge.r-project.org/projects/rprotobuf/ |
| mailing list | https://lists.r-forge.r-project.org/cgi-bin/mailman/listinfo/rprotobuf-yada |